



HEAVY DUTY STOP ARM WITH HOLD OPEN



HEAVY DUTY ARM

## **Features:**

- Cast iron body
- ANSI A156.4, Grade1 and ANSI A117.1 compliant
- UL listed
- ADA (Handicap) multi-sized closers with adjustable Spring Power for a Range of sizes, adjustable after installation
- Manufactured under ISO 9002 guidelines
- Available in a choice of three arm types, heavy duty STOP arm with hold open, heavy duty arm, or standard arm







Power adjustable door closer from size 1 through 6. This heavy duty, full-feature, multi-size door-closer is ideal for use in office buildings, retail stores, commercial buildings and schools. Supplied with peel-and-stick template for ease of installation.

## **Functions:**

- Tri-Style installation: installs regular, parallel arm or top jamb.
- Non-handed: installs on either side of door.
- Adjustable sweep and latch speeds: separate valves to adjust each speed.
- Adjustable backcheck: standard.

www.sparker.com

- Adjustable delayed action closing option available.
- Installs 3 ways: regular arm, parallel arm and top jamb.
- Cover: high impact, UL listed molded plastic full cover.
- Power of closer can be adjusted to conform to the requirements of the American with Disabilities Act (ADA) and as outlined in ANSI A 117.1 Specifications for Making Buildings and Facilities Accessible to, and Usable by the Physically Disabled.
- Door Opening: regular arm 120°, parallel arm 180° and top jamb 120°.

<b>Door Closer Size</b>	1	2	3	4	5	6
Max. Interior Door Size (in.)	32	36	42	48	54	58
Max. Exterior (Inswing) (in.)	28	32	36	42	48	52
Applicable Door Weight (lbs.) Power Adjustment Full 360° Clockwise	33-66	66-99	99-143	143-187	187-264	264-330
Turns of Adjustment Nut	-6	-3	0	3	7	12



## Quality Guaranteed!

One Source Buying Starts Here.